

宝钢厚板产品钢种价格表（2013年5月）

含标准规定冲击功

单位:元/吨(不含税)

品种	牌号	2013年5月份调整	2013年5月份价格	标准冲击温度
普通结构钢	Q235A	0	4220	
	Q235B	0	4270	20℃
	Q235C	0	4320	0℃
	Q235D	0	4420	-20℃
	SS330/SS400	0	4270	
	SM400A	0	4370	
	SM400B	0	4420	0℃
	SM400C	0	4470	0℃
	S235JR	0	4320	20℃
	S235J0	0	4370	0℃
	S235J2	0	4470	-20℃
	S275JR	0	4370	20℃
	S275J0	0	4420	0℃
	S275J2	0	4520	-20℃
	BE0650	0	4420	20℃
	A36	0	4270	
	低合金高强度结构钢	Q345A	0	4370
Q345B		0	4420	20℃
Q345C		0	4470	0℃
Q345D		0	4570	-20℃
Q345E		0	4670	-40℃
Q390A		0	4470	
Q390B		0	4520	20℃
Q390C		0	4570	0℃
Q390D		0	4670	-20℃
Q390E		0	4770	-40℃
Q420A		0	4520	
Q420B		0	4570	20℃
Q420C		0	4620	0℃
Q420D		0	4720	-20℃
Q420E		0	4820	-40℃
Q460C		0	4720	0℃
Q460D		0	4820	-20℃
Q460E		0	4920	-40℃
SS490		0	4470	
SM490A		0	4570	
SM490B		0	4620	0℃
SM490C		0	4670	0℃
S355JR		0	4420	20℃
S355J0		0	4470	0℃
S355J2		0	4570	-20℃
S355N		0	4470	协议
S355NL		0	4570	协议
A572Gr50	0	4420	协议	

	A572Gr60/65	0	4520	协议
桥梁结构钢	Q235qC	0	4420	0℃
	Q235qD	0	4520	-20℃
	Q235qE	0	4620	-40℃
	Q345qC	0	4570	0℃
	Q345qD	0	4670	-20℃
	Q345qE	0	4770	-40℃
	Q370qC	0	4620	0℃
	Q370qD	0	4720	-20℃
	Q370qE	0	4820	-40℃
	Q420qC	0	4720	0℃
	Q420qD	0	4820	-20℃
	Q420qE	0	4920	-40℃
	14MnNbq	0	5120	-40℃
	A709Gr50	0	4420	协议
建筑结构钢	Q235GJB	0	4370	20℃
	Q235GJC	0	4420	0℃
	Q235GJD	0	4520	-20℃
	Q235GJE	0	4620	-40℃
	Q345GJB	0	4520	20℃
	Q345GJC	0	4570	0℃
	Q345GJD	0	4670	-20℃
	Q345GJE	0	4770	-40℃
	Q390GJC	0	4670	0℃
	Q390GJD	0	4770	-20℃
	Q390GJE	0	4870	-40℃
	Q420GJC	0	4720	0℃
	Q420GJD	0	4820	-20℃
	Q420GJE	0	4920	-40℃
锅炉容器	Q245R	0	4370	0℃
	Q345R	0	4520	0℃
	16MnDR	0	4870	-40℃
	Q370R	0	4570	-20℃
	A515Gr55/60	0	4620	协议
	A515Gr65/70	0	4720	协议
	A516Gr55/60	0	4620	协议
	A516Gr65/70	0	4720	协议
船板	A	0	4330	20℃
	B	0	4430	0℃
	D	0	4630	-20℃
	E	0	4780	-40℃
	AH32	0	4580	0℃
	DH32	0	4730	-20℃
	EH32	0	4880	-40℃
	AH36	0	4780	0℃
	DH36	0	4930	-20℃
EH36	0	5130	-40℃	